



ELIMSTAT Overhead Ionizer

Specification Sheet

Part No. 4011714	ELIMSTAT Overhead Ionizer 100V (50/60 Hz)
Size: (W x H x D)	35 ½" x 4" x 6 ¼"
Weight	13 lbs.
Air Volume Output	230 CFM – 450 CFM (low to high)
Air Velocity at 2 Feet	Low – 350 FPM High – 700 FPM
Discharge Time	2.0 sec. At 24" (High Fan Speed)
Ion Balance (offset Voltage)	10 V +/-5
Effective Coverage	3' x 5' area
Audible Noise	59 to 60 dB (low to high)
Line Voltage (50/60 Hz)	100 VAC
MAX Current Draw	0.4 Amp

Features:

- Rapid static charge control
- Reliable performance
- Simple to Install
- Simple to operate

The ELIMSTAT overhead ionizer has been designed to control electrostatic charges in electronic assembly areas and Cleanroom environments. The Elimstat AC corona technology and high flow fans provide superior neutralization over an extended area. Features inherent balance and built-in emitter point cleaners and the ELIMSTAT Overhead is a low maintenance ionizer.

The ELIMSTAT Overhead features a recessed fan speed control. The fan speed control allows adjustment of the unit's air flow to suit the user's needs. Recessing the speed control discourages tampering once the desired air flow is set.